

# 安徽艾约塔硅油有限公司

# lota Corporation Ltd.

安徽省蚌埠市高新区兴中路 985 号日月

科技园

电话: 86-552-3827158

传真: 86-552-3822922

Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000

Tel: 86-552-3827158

Fax: 86-552-3822922

## TDS of IOTA ST4 high temp. resistant water-based nano ceramics coating

Product name: high temp. resistant water-based nano ceramics coating

Coating: Surface coating

## **Advantages**

- 1. The product is water-based coating, it's eco-friendly and no harmful to operators when applying.
- 2. According to special technology and formulation, the coating hardness is up to 9H, it has acid and alkali resistance, the cured coating is resistant to abrasion, scratches and graffiti, it's also anti-dust, oil, and dirty.
- 3. The product is resistant to temp. 900°C, it could be used as wooden material fireproof coating.

#### Technical index

Appearance: colorless to transparent liquid

Solid content: 35%

Coating thickness(wet film): 10-100 um Coating thickness(dry film): 1-50 um

Hardness(Chinese pencil): 9H

Adhesion: Grade 0

Appearance (after curing): colorless and transparent

Room temp. curing time: 30min surface drying, totally cured after 7 days

High temp. curing time: 150°C, 10min surface drying, the hardness will be 5-8H; totally

cured after 3hours, the hardness up to 9H.

### **Application**

Metal, glass, ceramics, wood furniture finish

ADD: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000 Tel: 86-552-3827158; Fax: 86-552-3822922 Website: www.iotasilica.com



# 安徽艾约塔硅油有限公司

# **lota Corporation Ltd.**Sunmoon industry park, 985 Xingzhong Road, Bengbu,

安徽省蚌埠市高新区兴中路 985 号日月

科技园 China 233000 电话: 86-552-3827158 Tel: 86-552-3827158

电话: 86-552-3827158 Tel: 86-552-3827158 传真: 86-552-3822922 Fax: 86-552-3822922

#### How to use?

- 1. Clean the surface of the material, sanding, remove the oil, to keep the surface dry and smooth.
- IOTA ST4 is water-based, without any solvent like alcohol and ester.
  The recommended coating method is brushing, showering, spinning and rolling.

#### **Notes**

- 1. The best performance can be achieved when the coating thickness (dry film) is less than 10um.
- 2. the opened products should be kept sealed enough.

## Package and transportation

- 1. Packed with 25kg plastic drum or 200kg iron drum.
- 2. Condition: packed in clean and dry container, sealed and kept in cool and dry place in 5-35°C.
- 3. Transported as non-dangerous goods.
- 4. Shelf lift: 6months.
- 5. Brand: IOTA

ADD: Sunmoon industry park, 985 Xingzhong Road, Bengbu, China 233000 Tel: 86-552-3827158; Fax: 86-552-3822922 Website: www.iotasilica.com